



# IFP DP101 / DP102 IFP DG101 / DG102

## Pump / Valve Combination Units for the Dump Truck and Trailer Industry



**IFP DP102**

- Air Shift Kits available
- Pressure to 2500 PSI
- Flows to 48 GPM @ 1800 RPM
- Built in relief valve
- Mounting & Parts Interchangeable with Parker / Commercial Intertech Permco, Muncie and all existing C101 / C102 installations

### OPERATING SPECIFICATIONS

Model No.	Max pressure	Flow @ 1800 RPM
IFP DP101-2.0" Gear	2500 psi	39 GPM
IFP DP101-2.5" Gear	2500 psi	48 GPM
IFP DP102-2.0" Gear	2500 psi	39 GPM
IFP DP102-2.5" Gear	2500 psi	48 GPM
IFP DG101-2" Gear	2500 psi	29 GPM
IFP DG102-2" Gear	2500 psi	29 GPM



**IFP DP101**

★ **Q.C. Assured**

### IN STOCK IFP GEAR PUMP ASSEMBLIES FOR THE REFUSE & MOBILE EQUIPMENT MARKET

**\*\*UNITS & PARTS REPLACE: PARKER / COMMERCIAL INTERTECH, PERMCO, MUNCIE & OTHERS \*\***

#### IFP IP2000 Series




#### Specifications

- 3.94 in<sup>3</sup>/rev
  - Shaft SAE-B 7/8-13 teeth
  - Mounting - SAE B 2 & 4 bolts
  - Maximum pressure - 2500 PSI
  - Maximum speed - 2500 RPM
- (Other shafts / mountings / displacements available)

#### APPLICATIONS

SNOW PLOWS  
HOISTS  
LIFT GATES  
TOW TRUCKS  
OTHER MOBILE  
EQUIPMENT

#### IFP IP5100 Series



#### Specifications

- 6.38 in<sup>3</sup>/rev
  - Shaft SAE-B 7/8-13 teeth
  - Mounting - SAE B 4 bolts
  - Maximum pressure - 3000 PSI
  - Maximum speed - 2400 RPM
- (Other shafts / mountings / displacements available)

#### APPLICATIONS

UTILITY TRUCKS  
AERIAL LIFTS  
TRANSFER AND  
LIVE FLOOR TRAILERS  
AND OTHER MOBILE  
EQUIPMENT

#### IFP IP7600 Series



#### Specifications

- 9.22 in<sup>3</sup>/rev
  - Shaft SAE-C 11/4-KEYED
  - Mounting - SAE C 4 bolts
  - Maximum pressure - 3000 PSI
  - Maximum speed - 2400 RPM
- (Other shafts / mountings / displacements available)

#### APPLICATIONS

REFUSE EQUIPMENT  
SOLID WASTE PACKERS  
OTHER MOBILE  
EQUIPMENT

**West Coast Toll Free: 1-800-432-6405 East Coast Toll Free: 1-800-363-8446**